



an EnerSys® company

Cordex® 250W

12VDC Modular Rectifier Shelf Systems



- 83A or 105A modular shelf systems for various 12VDC applications
- Convection cooled design for high reliability in harsh industrial environments
- Wide range AC input for multiple worldwide AC services
- Integrated system capability with shelf controller and DC distribution

The Cordex® series includes a complete range of modular 250W rectifier shelf systems to meet the needs of worldwide communications applications.

Cordex® 250W modular systems range from a 1.25kW bulk power 19" shelf with CXCI HP to a 1kW fully integrated 19" shelf power system with CXCI HP controller and bullet breaker distribution module.

The Cordex® 250W rectifier modules feature complete hot-swappability, high efficiency with power factor correction, and wide range input. Convection cooling and an ultra compact design also make Cordex® CXS shelf systems ideal for 12VDC applications.

Cordex® 250W 12VDC Modular Rectifier Shelf Systems

Cordex® 250W Modular Rectifier Shelf Systems

19/23" Shelf Systems



Cordex® 1.0kW Shelf Power System

P/N: 030-770-20-XXX

Rectifiers: 4x CXRC 12-250W

Controller: 1x CXG HP

Distribution: (4) AM Sytle Bullet Breakers (Factory Configured LVD)



Cordex® 1.25kW Bulk Power System

P/N: 030-783-20-XXX

Rectifiers: 5x CXRC-12-250W

Controller: Optional 1x CXG HP

Distribution: Bulk power for external distribution (optional LVD)

Electrical

Operating:	90-276VAC
Extended High:	276-310VAC (derated input power factor)
Extended Low:	60-90VAC (derate linearly to 0% output power)
Power Output:	250W at 120-240VAC Nominal
Input Current:	1.1 to 1.3A (208-240VAC) 3.4A Max @ 85VAC
Output Current:	20.8A @ 12VDC

Mechanical

4 Rectifier Shelf:

Dimensions: mm: 88H x 444W x 307D
inches: 3.5H x 17.5W x 12.1D

Weight: 6.39kg (15.2lbs)

5 Rectifier Shelf:

Dimensions: mm: 88H x 444W x 303D
inches: 3.5H x 17.5W x 12D

Weight: 8.5kg (18.7lbs)

Module:

Dimensions: mm: 88H x 71.6W x 242D
inches: 3.5H x 2.82W x 9.53D

Weight: 1.9kg (4.2lbs)

Note: Dimensions do not include mounting bracket

Communication Ports

CAN:	Interface to control rectifiers and smart peripherals
Ethernet:	10/100 Base-T for TCP/IP/SNMP features
USB:	Local backup and configuration transfer
I/O:	<ul style="list-style-type: none"> • 2 Digital Inputs (one used internally on systems with distribution) • 1 Voltage Sensor Input • 2 Temperature Sensor Inputs • 4 Dry Contact Outputs (one used internally on systems with LVD)

Environmental

Temperature:	Standard: -40 to 50°C (-40 to 122°F) Storage: -40 to 85°C (-40 to 185°F)
Humidity:	0 to 95% Relative Humidity (non condensing)
Elevation:	-500 to 3000m (-1640 to 9840ft)
Cooling:	Natural convection (vertical airflow)

Related Components

Rectifier:	010-587-20-040
Rectifier Blank:	613-465-W3
Controller:	0180056-001
6ft 1/4" Lug Temp Sensor:	747-028-20-071
6ft 3/8" Lug Temp Sensor:	747-082-20-071



an EnerSys® company

Alpha Technologies Services, Inc. USA: 3767 Alpha Way, Bellingham, WA 98226 Canada: 7700 Riverfront Gate, Burnaby, BC V5J 5M4

Toll Free North America: +1 800 322 5742 Outside US: +1 360 647 2360 Technical Support: +1 800 863 3364

For more information visit www.alpha.com

© 2020 Alpha Technologies Services, Inc. All Rights Reserved. Trademarks and logos are the property of Alpha Technologies Services, Inc. and its affiliates unless otherwise noted. Subject to revisions without prior notice. E. & O.E.

07/2020
#048-669-10 REV G