



an EnerSys® company

# Cordex® 400W

## 24VDC Modular Rectifier Shelf Systems



- Single shelf modular rectifier solution provides multiple 24V configurations up to 70A for various 24VDC applications
- Convection cooled design for high reliability in harsh industrial environments
- Wide range AC input for multiple worldwide AC services
- Integrated system capability with shelf controller and DC distribution

**The Cordex® series includes a complete range of modular 400W rectifier shelf systems to meet the needs of worldwide communications applications.**

Cordex® 400W modular systems range from a 2kW bulk power 19" shelf with CXCI HP to a 1.6kW fully integrated 19" shelf power system CXCI HP controller and distribution module.

The Cordex® 400W rectifier modules feature complete hot swappability, high efficiency with power factor correction, unique power limiting capability, and wide range input. Convection cooling and an ultra compact design also make Cordex® CXS shelf systems ideal for the communications industry.

# Cordex® 400W 24VDC Modular Rectifier Shelf Systems

## Cordex® 24-400W Rectifier Shelves

### 19/23" Shelf Systems



#### Cordex® 1.6kW Shelf Power System

P/N: 030-763-20-XXX

Rectifiers: 4x CXRC 24-400W

Controller: 1x CXG HP

Distribution: (4) AN Sytle Bullet Breakers (Factory Configured LVD)



#### Cordex® 2.0kW Bulk Power System

P/N: 030-773-20-XXX

Rectifiers: 5x CXRC 24-400W

Controller: Optional 1x CXG HP

Distribution: Bulk power for external distribution (optional LVD)

### Electrical

<b>Operating:</b>	90-276VAC
<b>Extended High:</b>	276-310VAC (derated input power factor)
<b>Extended Low:</b>	60-90VAC (derate linearly to 0% output power)
<b>Power Output:</b>	400W at 120-240VAC Nominal
<b>Input Current:</b>	1.7 to 2.0A (208-240VAC) 5.2A Max @ 90VAC
<b>Output Current:</b>	15A @ 24VDC 13.33A @ 27VDC

### Mechanical

<b>4 Rectifier Shelf:</b>	
<b>Dimensions:</b>	<b>mm:</b> 88H x 444W x 307D <b>inches:</b> 3.5H x 17.5W x 12.1D
<b>Weight:</b>	6.39kg (15.2lbs)
<b>5 Rectifier Shelf:</b>	
<b>Dimensions:</b>	<b>mm:</b> 88H x 444W x 303D <b>inches:</b> 3.5H x 17.5W x 12D
<b>Weight:</b>	8.5kg (18.7lbs)
<b>Module:</b>	
<b>Dimensions:</b>	<b>mm:</b> 88H x 71.6W x 242D <b>inches:</b> 3.5H x 2.82W x 9.53D
<b>Weight:</b>	1.6kg (3.6lbs)
Note: Dimensions do not include mounting bracket	
<b>Communication Ports</b>	
<b>CAN:</b>	Interface to control rectifiers and smart peripherals
<b>Ethernet:</b>	10/100 Base-T for TCP/IP/SNMP features
<b>USB:</b>	Local backup and configuration transfer
<b>I/O:</b>	<ul style="list-style-type: none"> <li>• 2 Digital Inputs (one used internally on systems with distribution)</li> <li>• 1 Voltage Sensor Input</li> <li>• 2 Temperature Sensor Inputs</li> <li>• 4 Dry Contact Outputs (one used internally on systems with LVD)</li> </ul>
<b>Environmental</b>	
<b>Temperature:</b>	<b>Standard:</b> -40 to 50°C (-40 to 122°F) <b>Storage:</b> -40 to 85°C (-40 to 185°F)
<b>Humidity:</b>	0 to 95% Relative Humidity (non condensing)
<b>Elevation:</b>	-500 to 3000m (-1640 to 9840ft)
<b>Cooling:</b>	Natural convection (vertical airflow)
<b>Related Components</b>	
<b>Rectifier:</b>	010-582-20-040
<b>Rectifier Blank:</b>	613-465-W3
<b>Controller:</b>	0180056-001
<b>6ft ¼" Lug Temp Sensor:</b>	747-028-20-071
<b>6ft ⅜" Lug Temp Sensor:</b>	747-082-20-071



an EnerSys® company

**Alpha Technologies Services, Inc.** USA: 3767 Alpha Way, Bellingham, WA 98226 Canada: 7700 Riverfront Gate, Burnaby, BC V5J 5M4  
Toll Free North America: +1 800 322 5742 Outside US: +1 360 647 2360 Technical Support: +1 800 863 3364  
For more information visit [www.alpha.com](http://www.alpha.com)

© 2020 Alpha Technologies Services, Inc. All Rights Reserved. Trademarks and logos are the property of Alpha Technologies Services, Inc. and its affiliates unless otherwise noted. Subject to revisions without prior notice. E. & O.E.

07/2020  
#048-670-10 REV G